

**Safety Data Sheet**


---

**1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**
**1.1 Product Identifier**

<b>Material Name:</b>	<b>Diesel (CAS 68334-30-5)</b>
<b>REACH Registration No.:</b>	01-2119484664-27
<b>Synonyms:</b>	Diesel AGO, Diesel MK3 BIO 0%, Diesel MK3 Winter, Diesel D-10/D-32, Diesel E, DB 3, E10, E32, EN590 diesel, EN590 ULSD, E10F, E32F, Fuel oil light, Fuel oil environmental, Gasoil IGO, Marine gas oil, ULSD 10

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Product Use:** Heating, marine fuels, fuel.  
 Distribution of substance, industrial  
 Formulation & (re) packing of the substances and mixtures, industrial  
 Use as a fuel, industrial  
 Use as a fuel, professional  
 Use as a fuel, consumer

**Uses Advised Against:** Applications that are not registered and risk assessed.

**1.3 Details of the supplier of the substance or mixture**

**Manufacturer/Supplier:** Swea Energi AB  
 Nygatan 10 C  
 434 30 Kungsbacka

**Telephone:** +46 (0) 20 450 800

**Email Contact for MSDS:** info@sweaenergi.se

**1.4 Emergency Telephone Number:** 112 SOS Alarm  
 Swedish Poisons Information Centre: +46 (0)8 331231

---

**2. HAZARDS IDENTIFICATION**
**2.1 Classification of substance or mixture**

**Product definition:** Substance

## Safety Data Sheet

---

Regulation (EC) No 1272/2008 (CLP)	
Hazard classes / Hazard categories	Hazard Statement
Flammable liquids, Category 3	H226
Aspiration hazard, Category 1	H304
Skin corrosion/irritation, Category 2	H315
Acute toxicity, Category 4; Inhalation	H332
Carcinogenicity, Category 2	H351
Specific target organ toxicity - repeated exposure, Category 2; Blood.; Liver.; Thymus.	H373
Chronic hazards to the aquatic environment, Category 2	H411

Classification triggering components:

Contains petroleum distillates.

### 2.2 Label Elements

#### Labeling according to Regulation (EC) No 1272/2008

Symbol(s):



Signal Words:

Danger

CLP Hazard Statements:

PHYSICAL HAZARDS:

H226: Flammable liquid and vapor.

HEALTH HAZARDS:

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS:

H411: Toxic to aquatic life with long lasting effects.

CLP Precautionary statements

PREVENTION:

## Safety Data Sheet

---

P201, P210, P240, P241, P242, P243, P260, P264, P270, P273, P280

**RESPONSE:**

P301+P310, P302+P352, P303+P361+P353, P304+P340, P308+P313, P312, P331, P332+P313, P370+P378, P391

**STORAGE:**

P403+P235, P403+P233, P405

**DISPOSAL:**

P501

For more information regarding CLP Precautionary statements, see chapter 16.

### 2.3 Other Hazards

**Safety Hazards:**

May ignite on surfaces at temperatures above auto-ignition temperature. Vapour in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto ignition temperature, where vapour concentrations are within the flammability range. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire.

The substance does not fulfil all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB. PBT =Persistent, Bioaccumulative, Toxic. vPvB = very Persistent, very Bioaccumulative.

**Other information:**

This product is intended for use in closed systems only.

---

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substance

**Cas nr.** 68334-30-5

**Preparation Description:** A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C25 and boiling in the range of approximately 160 to 400°C.

Product is not a mixture according regulation 1907/2006/EC.

**Safety Data Sheet**

---

**Hazardous Components****Classification of components according to Regulation (EC) No 1272/2008**

Chemical Name	CAS No.	EINECS	REACH Registration No.	Conc. vol%
Fuels, diesel	68334-30-5	269-822-7	01-2119484664-27	100

Chemical Name	Hazard Class & Category	Hazard Statement
Fuels, diesel	Flam. Liq., 3; Asp. Tox., 1; Acute Tox., 4; Skin Corr., 2; Carc., 2; STOT RE, 2; Aquatic Chronic, 2	H226; H304; H315; H332; H351; H373; H411

**3.2 Mixtures:** Not applicable.

**Additional Information:** Colours and markers can be used to indicate tax status and prevent fraud.

---

**4. FIRST AID MEASURES****4.1 Description of First Aid Measures**

- Inhalation:** Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- Skin contact:** Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
- Eye contact:** Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
- Ingestion:** If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 38 °C, shortness of breath, chest congestion or continued coughing or wheezing. Give nothing by mouth.
- 4.2 Most important symptoms/effects, acute & delayed:** If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure.

## Safety Data Sheet

---

Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

### 4.3 Indication of immediate medical attention and special treatment needed:

Treat symptomatically.

---

## 5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

**5.1 Extinguishing Media:** Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

**Unsuitable Extinguishing Media:** Do not use water in a jet. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

**5.2 Special hazards arising from substance or mixture:** Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Oxides of sulphur. Unidentified organic and inorganic compounds. Carbon monoxide may be evolved if incomplete combustion occurs. Will float and can be reignited on surface water. Flammable vapours may be present even at temperatures below the flash point.

**5.3 Advice for fire-fighters:** Wear full protective clothing and self-contained breathing apparatus.

**Additional Advice:** Keep adjacent containers cool by spraying with water.

---

## 6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations. Evacuate the area of all non-essential personnel. Ventilate contaminated area thoroughly.

**6.1 Personal Precautions, Protective Equipment and Emergency Procedures:** Do not breathe fumes, vapour. Do not operate electrical equipment.

**6.2 Environmental Precautions:** Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and firefighting water) to

## Safety Data Sheet

---

avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

### 6.3 Methods and Material for Containment

For small liquid spills, transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Absorb with a suitable absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Place in a suitable container with clearly marked container for disposal or recovery in accordance with local regulations.

For large liquid spills, transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Absorb with a suitable absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.

### Additional Advice:

Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Local authorities should be advised if significant spillages cannot be contained. Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

---

## 7. HANDLING AND STORAGE

### General Precautions:

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Air-dry contaminated clothing in a well-ventilated area before laundering. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier.

## Safety Data Sheet

---

<b>7.1 Precautions for Safe Handling:</b>	Avoid inhaling vapour and/or mists. Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire. Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks. Earth all equipment. Avoid prolonged or repeated contact with skin. When using do not eat or drink. The vapour is heavier than air, spreads along the ground and distant ignition is possible.
<b>7.2 Conditions for safe storage, including any incompatibilities:</b>	Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. The vapour is heavier than air. Beware of accumulation in pits and confined spaces. Keep in a bunded area with a sealed (low permeability) floor, to provide containment against spillage. Prevent ingress of water.
<b>7.3 Specific End Uses:</b>	Please refer to Ch16 and/or the annexes for the registered uses under REACH.
<b>Additional Information:</b>	Exposure to this product should be reduced as low as reasonably practicable. Ensure that all local regulations regarding handling and storage facilities are followed.
<b>Product Transfer:</b>	Avoid splash filling. Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Keep containers closed when not in use. Do not use compressed air for filling, discharging or handling. Contamination resulting from product transfer may give rise to light hydrocarbon vapour in the headspace of tanks that have previously contained gasoline. This vapour may explode if there is a source of ignition. Partly filled containers present a greater hazard than those that are full, therefore handling, transfer and sampling activities need special care.
<b>Recommended Materials:</b>	For containers, or container linings use mild steel, stainless steel.
<b>Unsuitable Materials</b> :	Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer.
<b>Container Advice:</b>	Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar

**Safety Data Sheet**

operations on or near containers.

**Other Information:** Ensure that all local regulations regarding handling and storage are followed.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

**8.1 Control Parameters****Occupational Exposure Limits**

Not established

**Biological Exposure Index (BEI)**

No biological limit allocated.

**Derived No Effect Levels (DNEL)**

Component	Exposure Route	Exposure Type Long/short	Application Area	Value
Fuels, diesel	Inhalation	Acute, systemic effects	Worker	4300 mg/m <sup>3</sup> / 15 min (aerosol)
	Dermal	Long term, systemic effects	Worker	2,9 mg/kg 8 h
	Inhalation	Long term, systemic effects	Worker	68 mg/m <sup>3</sup> /8 h (aerosol)
	Inhalation	Acute, systemic effects	Consumer	2600 mg/m <sup>3</sup> /15 min (aerosol)
	Dermal	Long term, systemic effects	Consumer	1,3 mg/kg 24 h
	Inhalation	Long term, systemic effects	Consumer	20 mg/m <sup>3</sup> /24 h (aerosol)

PNEC (Predicted No-Effect Concentration) related information:

**8.2 Exposure Controls  
General Information:**

Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Use sealed systems as far as possible. Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Local exhaust ventilation is recommended. Eye washes and showers for emergency use.



## Safety Data Sheet

---

### Occupational Exposure Controls

<b>Personal Protective Equipment:</b>	Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
<b>Eye Protection:</b>	Chemical splash goggles (chemical monogoggles). Approved to EU Standard EN166.
<b>Hand Protection:</b>	Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, and dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Select gloves tested to a relevant standard (e.g. EN374 for chemical resistance and EN407 for heat resistance). For prolonged or repeated contact, use nitrile gloves (breakthrough time of > 240 minutes.) For incidental contact/splash, use Neoprene/PVC gloves.
<b>Body protection:</b>	Chemical resistant gloves/gauntlets, boots, and apron (where risk of splashing).
<b>Respiratory Protection:</b>	If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. All respiratory protection equipment and use must be in accordance with local regulations. Select a filter suitable for organic gases and vapours (boiling point >65 °C) meeting EN14387.
<b>Monitoring Methods:</b>	Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

### Environmental Exposure Controls

<b>Environmental exposure control measures:</b>	Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.
---	--

## Safety Data Sheet

---

### Consumer Exposure Controls

**Exposure Control Measures for Consumers:** If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes. Do not ingest. If swallowed then seek immediate medical assistance.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

According to Swedish Standard SS EN 590:2009 and SS 15 54 10:2011.

<b>Appearance:</b>	Clear liquid, colourless, yellow or green
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	-
<b>pH:</b>	Not applicable
<b>Melting point/freezing point:</b>	< -10 °C
<b>Initial boiling point and boiling range:</b>	160 - 370°C
<b>Flash point:</b>	>56 °C
<b>Evaporation rate:</b>	-
<b>Flammability (solid, gas)</b>	-
<b>Upper/lower flammability or explosive limits:</b>	0,6 – 7,5 % (V)
<b>Vapour pressure, at 37,8 °C:</b>	<0,5 kPa
<b>Vapour density:</b>	-
<b>Relative density:</b>	820 - 860 kg/m <sup>3</sup>
<b>Solubility(ies):</b>	Not solubility
<b>Partition coefficient: n-octanol/water:</b>	-
<b>Auto-ignition temperature:</b>	> 225°C
<b>Decomposition temperature:</b>	-
<b>Kinematics Viscosity, 40°C</b>	1 - 5 mm <sup>2</sup> /s
<b>Explosive properties:</b>	Not considered to be explosive
<b>Oxidising properties:</b>	Not considered to oxidise

### 9.2 Other Information

**Other Information:** Not applicable.

---

## 10. STABILITY AND REACTIVITY

**10.1 Reactivity:** The product is not considered to be reactive.

## Safety Data Sheet

---

<b>10.2 Chemical Stability:</b>	Stable under normal conditions of use.
<b>10.3 Possibility of Hazardous Reactions:</b>	Under normal conditions of storage and use, there are no dangerous reactions.
<b>10.4 Conditions to Avoid:</b>	Avoid heat, sparks, open flames and other ignition sources.
<b>10.5 Incompatible Materials:</b>	Strong oxidising agents.
<b>10.6 Hazardous Decomposition Product:</b>	Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

## 11. TOXIKOLOGISK INFORMATION

### 11.1 Information on Toxicological effects

<b>Basis for Assessment:</b>	Information given is based on product data, knowledge of the components and the toxicology of similar products.
<b>Acute Oral Toxicity:</b>	Low toxicity: LD50 >5000 mg/kg, Rat.
<b>Acute Dermal Toxicity:</b>	Low toxicity: LD50 >2000 mg/kg, Rabbit.
<b>Acute Inhalation Toxicity:</b>	Harmful by inhalation: LC50 > 1.0 - ≤ 5.0 mg/l/4 h, Rat.
<b>Skin Corrosion/Irritation:</b>	Irritating to skin.
<b>Serious Eye Damage/Irritation:</b>	Expected to be slightly irritating.
<b>Respiratory Irritation:</b>	Inhalation of vapours or mists may cause irritation to the respiratory system.
<b>Respiratory or Skin Sensitisation:</b>	Not a skin sensitizer.
<b>Aspiration Hazard:</b>	Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.
<b>Germ Cell Mutagenicity:</b>	Positive in in-vitro, but negative in in-vivo mutagenicity assays.
<b>Carcinogenicity:</b>	Limited evidence of carcinogenic effect. Repeated skin contact has resulted in irritation and skin cancer in animals.
<b>Reproductive and Developmental Toxicity:</b>	Not expected to impair fertility. Not classified as a developmental toxicant.
<b>Specific target organ toxicity - single exposure:</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure:</b>	May cause damage to organs through prolonged or repeated exposure. Blood. Thymus. Liver.

---

## 12. ECOLOGICAL INFORMATION

<b>Basis for Assessment:</b>	Information given is based on knowledge of the components and
------------------------------	---

## Safety Data Sheet

---

	the ecotoxicology of similar products.
<b>12.1 Acute Toxicity</b>	
<b>Acute Toxicity</b>	Expected to be toxic: LL/EL/IL50 1-10 mg/l (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract).
<b>Fish</b>	Expected to be toxic: LL/EL/IL50 1-10 mg/l
<b>Aquatic Invertebrates</b>	Expected to be toxic: LL/EL/IL50 1-10 mg/l
<b>Algae</b>	Expected to be toxic: LL/EL/IL50 1-10 mg/l
<b>Microorganisms</b>	Expected to be practically non-toxic: LL/EL/IL50 > 100 mg/l
<b>Chronic Toxicity</b>	NOEC = No Observable Effect Concentration NOEL = No Observable Effect Level
<b>Fish</b>	NOEC/NOEL expected to be > 0.01 - <= 0.1 mg/l (based on modelled data)
<b>Aquatic Invertebrates</b>	NOEC/NOEL expected to be > 0.1 - <= 1.0 mg/l (based on modelled data)
<b>12.2 Persistence and degradability:</b>	Readily biodegradable in water.
<b>12.3 Bioaccumulative Potential:</b>	Contains constituents with the potential to bioaccumulate.
<b>12.4 Mobility:</b>	Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day. If product enters soil, one or more constituents will be mobile and may contaminate groundwater. Floats on water. Large volumes may penetrate soil and could contaminate groundwater.
<b>12.5 Results of PBT and vPvB assessment:</b>	The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB. PBT = Persistent, Bioaccumulative, Toxic. vPvB = very Persistent, very Bioaccumulative.
<b>12.6 Other adverse effects:</b>	Films formed on water may affect oxygen transfer and damage organisms.

---

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste Treatment Methods

<b>Material Disposal:</b>	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a
---------------------------	--

**Safety Data Sheet**

---

recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

**Container Disposal:**

Send to drum recoverer or metal reclaimer. Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned drums. Do not pollute the soil, water or environment with the waste container. Comply with any local recovery or waste disposal regulations.

**Local Legislation:**

EU Waste Disposal Code (EWC):

13 07 01 Fuel oil and diesel

13 07 03 Other fuels (including mixtures)

The number given to waste is associated with the appropriate usage. The user must decide if their particular use results in another waste code being assigned. Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

---

**14. TRANSPORT INFORMATION****ADR/RID**

<b>UN No:</b>	<b>Land transport</b>
<b>UN Proper Shipping Name:</b>	1202
<b>Transport Hazard Class:</b>	GAS OIL
<b>Packing group:</b>	3
<b>Environmental Hazard:</b>	III
	Yes

**ADN**

<b>UN No:</b>	<b>Inland waterways transport</b>
<b>UN Proper Shipping Name:</b>	1202
<b>Transport Hazard Class:</b>	GAS OIL
<b>Packing group:</b>	3
<b>Environmental Hazard:</b>	III
	Yes

**IMDG**

<b>UN No:</b>	<b>Sea transport</b>
<b>UN Proper Shipping Name:</b>	1202
<b>Transport Hazard Class:</b>	GAS OIL
<b>Packing group:</b>	3
<b>Environmental Hazard:</b>	III
	Yes

**Safety Data Sheet**

---

<b>IATA</b>	<b>Air transport</b>
UN No:	1202
UN Proper Shipping Name:	GAS OIL
Transport Hazard Class:	3
Packing group:	III
Environmental Hazard:	Yes

**Sea (Annex II of MARPOL 73/78 and the IBC code)**

Pollution Category	Not applicable.
Ship Type	Not applicable.
Product Name	Not applicable.
Special Precaution	Not applicable.

**Additional Information:** MARPOL Annex I rules apply for bulk shipments by sea.  
MARPOL Annex II not applicable.

---

**15. REGULATORY INFORMATION**

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Regulation (EC) No 1907/2006 (REACH).  
EU Regulation (EC) No 1272/2008 Classification, labelling and packaging of chemical substances and mixtures (CLP).

**15.2 Chemical Safety Assessment**

A Chemical Safety Assessment was performed for this substance.

---

**16. OTHER INFORMATION****CLP Hazard Statements**

H226: Flammable liquid and vapor.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H332: Harmful if inhaled.  
H351: Suspected of causing cancer.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H411: Toxic to aquatic life with long lasting effects.

**CLP Precautionary statements**

P201: Obtain special instructions before use  
P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking  
P240: Ground/bond container and receiving equipment

## Safety Data Sheet

---

P241: Use explosion-proof electrical/ventilation/ lightning equipment

P242: Use only non-sparing tools

P243: Take precautionary measures against static discharge

P260: Do not breathe dust/fume/gas/vapours/spray

P264: Wash hands thoroughly after handling

P270: Do not eat, drink or smoke when using this product

P273: Avoid release to the environment

P280: Wear protective gloves/clothing/eye protection

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302+P352: IF ON SKIN: Wash with plenty of soap and water

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P308+P313: IF exposed or concerned: Get medical advice/attention

P312: Call a POISON CENTER or doctor/physician if you feel unwell

P331: Do NOT induce vomiting

P332+P313: If skin irritation occurs: Get medical advice/attention

P370+P378: In case of fire: Use water spray or foam for extinction

P391: Collect spillage

P403+P233: Store in a well-ventilated place. Keep container tightly closed

P403+P235: Store in a well-ventilated place. Keep cool

P405: Store locked up

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

### Recommended Restrictions on Use (Advice Against):

This product must not be used in applications other than those recommended in Section 1, without first seeking the advice of the supplier. This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser.

### Additional Information:

This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters.

### Further Information

This product is intended for use in closed systems only.

### MSDS Distribution:

The information in this document should be made available to all who may handle the product.

## Safety Data Sheet

---

**MSDS Version Number:** 1.5

**MSDS Effective Date:** 12.09.2016

**Disclaimer:** This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.



## Safety Data Sheet

---

### Table of Contents exposure scenarios

#### Identified Uses according to the Use Descriptor System

**Uses – Worker**

**Title** 1. Manufacture of substance  
- Industrial

**Uses – Worker**

**Title** 2. Use as an intermediate  
- Industrial

**Uses – Worker**

**Title** 3. Distribution of substance  
- Industrial

**Uses – Worker**

**Title** 4. Formulation & (re)packing of substances and mixtures  
- Industrial

**Uses – Worker**

**Title** 5. Use as a fuel  
- Industrial

**Uses – Worker**

**Title** 6. Use as a fuel  
- Professional

**Use – Consumer**

**Title** 7. Use as a fuel  
- Consumer

## Safety Data Sheet

---

### Abbreviation:

SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU8 - Manufacture of bulk, large scale chemicals (including petroleum products)

SU9 - Manufacture of fine chemicals

SU 10 - Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SU21 - Consumer uses: Private households (= general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

PC13 - Fuels

PROC1 - Use in closed process, no likelihood of exposure

PROC2 - Use in closed, continuous process with occasional controlled exposure

PROC3 - Use in closed batch process (synthesis or formulation)

PROC4 - Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5 - Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC14 - Production of preparations or articles by tableting, compression, extrusion, pelletisation

PROC15 - Use as laboratory reagent

PROC16 - Using material as fuel sources, limited exposure to unburned product to be expected

ERC1 - Manufacture of substances

ERC2 - Formulation of preparations

ERC3 - Formulation in materials

ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC5 - Industrial use resulting in inclusion into or onto a matrix

ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)

ERC6b - Industrial use of reactive processing aids

ERC6c - Industrial use of monomers for manufacture of thermo-plastics

ERC6d - Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

ERC7 - Industrial use of sub-stances in closed systems

ERC9a - Wide dispersive indoor use of substances in closed systems

ERC9b - Wide dispersive outdoor use of substances in closed systems

## Safety Data Sheet

## Exposure Scenario – Worker

SECTION 1	EXPOSURE SCENARIO TITLE
<b>Title</b>	1. Manufacture of substance - Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC4, ESVOC SpERC 1.1.v1
<b>Scope of process</b>	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
-----------	---

Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of substance in product.	Covers percentage substance in the product up to 100 % (unless stated differently).
<b>Frequency and Duration of Use</b>	
	Covers daily exposures up to 8 hours (unless stated differently).
<b>Other Operational Conditions affecting Exposure</b>	
	Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene has been implemented.

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities.	Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions.

## Safety Data Sheet

General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves tested to EN374 (nitrile gloves have the best protection for diesel), if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
General exposures (open systems)	Wear suitable gloves tested to EN374 (nitrile).
Process sampling	No other specific measures identified.
Bulk closed loading and unloading	Wear suitable gloves tested to EN374 (nitrile).
Bulk open loading and unloading	Wear suitable gloves tested to EN374 (nitrile).
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (nitrile) in combination with 'basic' employee training.
Laboratory activities	No other specific measures identified.
Bulk product storage	Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	2.8E+07
Fraction of Regional tonnage used locally:	0.021
Annual site tonnage (tonnes/year):	6.0E+05
Maximum daily site tonnage (kg/day):	2.0E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1.0E+02

**Safety Data Sheet**

Release fraction to wastewater from process (initial release prior to RMM):	3.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	90.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	94.1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d):	3.3E+06
Assumed domestic sewage treatment plant flow (m3/d)	10000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
During manufacturing no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
During manufacturing no waste of the substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 - Environment</b>
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

**Safety Data Sheet**

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p>	
<b>Section 4.2 - Environment</b>	
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>	
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>	
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>	
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a>).</p>	

## Safety Data Sheet

## Exposure Scenario – Worker

SECTION 1	EXPOSURE SCENARIO TITLE
<b>Title</b>	2. Use as an intermediate - Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC6A, ESVOC SpERC 6.1a.v1
<b>Scope of process</b>	Use of substance as an intermediate within closed or contained systems (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
-----------	---

Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 0,5 kPa at STP
Concentration of substance in product.	Covers percentage substance in the product up to 100 % (unless stated differently).
<b>Frequency and Duration of Use</b>	
	Covers daily exposures up to 8 hours (unless stated differently).
<b>Other Operational Conditions affecting Exposure</b>	
	Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene has been implemented.
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures applicable to all activities	Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions.

## Safety Data Sheet

General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves tested to EN374 (nitrile gloves have the best protection for diesel), if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
General exposures (open systems)	Wear suitable gloves tested to EN374 (nitrile).
Process sampling	No other specific measures identified.
Bulk closed loading and unloading	Wear suitable gloves tested to EN374 (nitrile).
Bulk open loading and unloading	Wear suitable gloves tested to EN374 (nitrile).
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (nitrile) in combination with 'basic' employee training.
Laboratory activities	No other specific measures identified.
Bulk product storage	Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	3.5E+05
Fraction of Regional tonnage used locally:	0.043
Annual site tonnage (tonnes/year):	1.5E+04
Maximum daily site tonnage (kg/day):	5.0E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1.0E-03



**Safety Data Sheet**

Release fraction to wastewater from process (initial release prior to RMM):	3.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	51.7
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	94.1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	4.1E+05
Assumed domestic sewage treatment plant flow (m3/d)	2000
<b>Conditions and measures related to external treatment of waste for disposal</b>	
This substance is consumed during use and no waste of substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 - Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

**Safety Data Sheet**

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p>	
<b>Section 4.2 -Environment</b>	
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>	
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>	
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>	
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a>).</p>	

## Safety Data Sheet

## Exposure Scenario – Worker

SECTION 1	EXPOSURE SCENARIO TITLE
<b>Title</b>	3. Distribution of substance - Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC2, ERC3, ERC4, ERC5, ERC6A, ERC6B, ERC6C, ERC6D, ERC7, ESVOC SpERC 1.1b.v1
<b>Scope of process</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
-----------	---

Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 0.5 kPa at STP
Concentration of substance in product.	Covers percentage substance in the product up to 100 % (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene has been implemented.	

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities	Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions.

## Safety Data Sheet

General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves tested to EN374 (nitrile gloves have the best protection for diesel) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
General exposures (open systems)	Wear suitable gloves tested to EN374 (nitrile).
Process sampling.	No other specific measures identified.
Bulk closed loading and unloading	Wear suitable gloves tested to EN374 (nitrile).
Bulk open loading and unloading	Wear suitable gloves tested to EN374 (nitrile).
Drum and small package filling	Wear suitable gloves tested to EN374 (nitrile).
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (nitrile) in combination with 'basic' employee training.
Laboratory activities	No other specific measures identified.
Storage	Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	2.8E+07
Fraction of Regional tonnage used locally:	0.002
Annual site tonnage (tonnes/year):	5.6E+04
Maximum daily site tonnage (kg/day):	1.9E+05
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	

## Safety Data Sheet

Release fraction to air from process (initial release prior to RMM):	1.0E-03
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-06
Release fraction to soil from process (initial release prior to RMM):	1.0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	9.6
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	94.1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	2.9E+06
Assumed domestic sewage treatment plant flow (m3/d)	2000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 - Environment</b>
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## Safety Data Sheet

---

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p>	
<b>Section 4.2 - Environment</b>	
<p>Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.</p>	
<p>Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.</p>	
<p>Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.</p>	
<p>Further details on scaling and control technologies are provided in SpERC factsheet (<a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a>).</p>	

## Safety Data Sheet

## Exposure Scenario – Worker

SECTION 1	EXPOSURE SCENARIO TITLE
<b>Title</b>	4. Formulation & (re)packing of substances and mixtures - Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU10 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 <b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1
<b>Scope of process</b>	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
-----------	---

Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 0.5 kPa at STP
Concentration of substance in product.	Covers percentage substance in the product up to 100 % (unless stated differently).
<b>Frequency and Duration of Use</b>	
	Covers daily exposures up to 8 hours (unless stated differently).
<b>Other Operational Conditions affecting Exposure</b>	
	Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene has been implemented.

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities	Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions.

## Safety Data Sheet

General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves tested to EN374 (nitrile gloves have the best protection for diesel), if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
General exposures (open systems)	Wear suitable gloves tested to EN374 (nitrile).
Process sampling.	No other specific measures identified.
Drum/batch transfers	Use drum pumps or carefully pour from container. Wear suitable gloves tested to EN374 (nitrile) in combination with 'basic' employee training.
Bulk transfers	Handle substance within a closed system. Wear suitable gloves tested to EN374 (nitrile).
Mixing operations (open systems)	Provide extract ventilation to points where emissions occur. Wear chemically resistant gloves (nitrile) in combination with 'basic' employee training.
Production or preparation or articles by tableting, compression, extrusion or pelletisation	Wear suitable gloves tested to EN374 (nitrile).
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (nitrile) in combination with 'basic' employee training.
Laboratory activities	No other specific measures identified.
Storage	Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	2.8E+07
Fraction of Regional tonnage used locally:	0.0011
Annual site tonnage (tonnes/year):	3.0E+04



## Safety Data Sheet

Maximum daily site tonnage (kg/day):	1.0E+05
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements):	1.0E-02
Release fraction to wastewater from process (initial release prior to RMM):	2.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	60.0
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	94.1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	6.8E+05
Assumed domestic sewage treatment plant flow (m3/d)	2000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

**Safety Data Sheet**

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	
<b>Section 3.2 - Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p>	
<b>Section 4.2 - Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org/en/reach-for-industries-libraries.html">http://cefic.org/en/reach-for-industries-libraries.html</a> ).	

## Safety Data Sheet

## Exposure Scenario – Worker

SECTION 1	EXPOSURE SCENARIO TITLE
<b>Title</b>	5. Use as a fuel - Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.12a.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
-----------	---

Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 0.5 kPa at STP
Concentration of substance in product.	Covers percentage substance in the product up to 100 % (unless stated differently).
<b>Frequency and Duration of Use</b>	
	Covers daily exposures up to 8 hours (unless stated differently).
<b>Other Operational Conditions affecting Exposure</b>	
	Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene has been implemented.

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities	Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions.
General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves tested to EN374 (nitrile gloves have the best protection for diesel) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training

## Safety Data Sheet

	to prevent / minimise exposures and to report any skin problems that may develop.
Drum/batch transfers	Wear suitable gloves tested to EN374 (nitrile).
Bulk transfers	Wear suitable gloves tested to EN374 (nitrile).
Use as a fuel (closed systems)	No other specific measures identified.
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Handle substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	4.5E+06
Fraction of Regional tonnage used locally:	0.34
Annual site tonnage (tonnes/year):	1.5E+06
Maximum daily site tonnage (kg/day):	5.0E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements):	5.0E-04
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-07
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Onsite waste water treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	95
Treat onsite wastewater (prior to receiving water discharge) to provide	97.7

**Safety Data Sheet**

the required removal efficiency of >= (%)	
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	60.4
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	97.7
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	5.5E+06
Assumed domestic sewage treatment plant flow (m3/d)	2000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 - Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p>	

**Safety Data Sheet**

---

**Section 4.2 -Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

## Safety Data Sheet

## Exposure Scenario – Worker

SECTION 1	EXPOSURE SCENARIO TITLE
<b>Title</b>	6. Use as a fuel - Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 <b>Environmental Release Categories:</b> ERC9A, ERC9B, ESVOC SpERC 9.12b.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
-----------	---

Section 2.1	Control of Worker Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 0.5 kPa at STP
Concentration of substance in product.	Covers percentage substance in the product up to 100 % (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene has been implemented.	

Contributing Scenarios	Risk Management Measures
General measures applicable to all activities	Control any potential exposure using measures such as contained systems, properly designed and maintained facilities and a good standard of general ventilation. Drain down systems and transfer lines prior to breaking containment. Drain down and flush equipment where possible prior to maintenance. Where there is potential for exposure: Ensure relevant staff are informed of exposure potential and aware of basic actions to minimise exposures; ensure suitable personal protective equipment is available; clear up spills and dispose of waste in accordance with regulatory requirements; monitor effectiveness of control measures; provide regular health surveillance as appropriate; identify and implement corrective actions.

## Safety Data Sheet

General measures (skin irritants)	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves tested to EN374 (nitrile gloves have the best protection for diesel) if hand contact with substance is likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
Drum/batch transfers	Wear suitable gloves tested to EN374 (nitrile).
Bulk transfers	Wear suitable gloves tested to EN374 (nitrile).
Refuelling	Wear suitable gloves tested to EN374 (nitrile).
Use as a fuel (closed systems)	Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour), or ensure operation is undertaken outdoors.
Equipment cleaning and maintenance	Drain down system prior to equipment break-in or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage	Store substance within a closed system.

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	6.7E+06
Fraction of Regional tonnage used locally:	5.0E-04
Annual site tonnage (tonnes/year):	3.3E+03
Maximum daily site tonnage (kg/day):	9.2E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	1.0E-04
Release fraction to wastewater from wide dispersive use:	1.0E-05
Release fraction to soil from wide dispersive use (regional only):	1.0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	



## Safety Data Sheet

<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	8.3
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of (%)	0
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	94.1
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	94.1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1.4E+05
Assumed domestic sewage treatment plant flow (m3/d)	2000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 - Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
<p>Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.</p> <p>Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.</p> <p>Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.</p> <p>Risk Management Measures are based on qualitative risk characterisation.</p>	

**Safety Data Sheet**

---

**Section 4.2 -Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).

## Safety Data Sheet

## Exposure Scenario – Consumer

SECTION 1	EXPOSURE SCENARIO TITLE
<b>Title</b>	7. Use as a fuel - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Category:</b> PC13 <b>Environmental Release Categories:</b> ERC9A, ERC9B, ESVOc SpERC 9.12b.v1
<b>Scope of process</b>	Covers consumer uses in liquid fuels.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
-----------	---

Section 2.1	Control of Consumer Exposure
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 Pa
Concentration of substance in product.	Unless otherwise stated: Covers concentrations up to 100 %
<b>Amounts Used</b>	
Unless otherwise stated:	
for each use event, covers amount up to (g):	37 500
covers skin contact area (cm <sup>2</sup> ):	420
<b>Frequency and duration of use</b>	
Unless otherwise stated:	
covers use up to (times/day of use):	0.143
covers use up to (hours/events):	2

Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Fuels. Liquid: Automotive Refuelling.	Covers concentration up to (%): 100 %
	Covers use up to (days/year): 52 day/year
	Covers use up to 1 times/day of use
	Covers skin contact area 210 cm <sup>2</sup>
	For each use event, covers amount up to 37,500 g.
	Covers outdoor use.
	Covers use in room size of 100 m <sup>3</sup>
	Covers exposure up to 0.05 hours/event
Fuels. Liquid Garden Equipment - Use.	Covers concentration up to (%): 100 %
	Covers use up to 26 day/year

## Safety Data Sheet

	Covers use up to 1 times/day of use
	For each use event, covers amount up to 750 g.
	Covers outdoor use.
	Covers use in room size of 100 m <sup>3</sup>
	Covers exposure up to 2.00 hours/event
Fuels. Liquid: Garden Equipment - Refuelling.	Covers concentrations up to 100 %
	Covers use up to 26 day/year
	Covers use up to 1 times/day of use
	Covers skin contact area 420 cm <sup>2</sup>
	For each use event, covers amount up to 750 g.
	Covers use in a one car garage (34 m <sup>3</sup> ) under typical ventilation.
	Covers use in room size of 34 m <sup>3</sup>
	Covers exposure up to 0.03 hours/event

<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.6E+07
Fraction of Regional tonnage used locally:	5.0E-04
Annual site tonnage (tonnes/year):	8.2E+03
Maximum daily site tonnage (kg/day):	2.3E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	1.0E-04
Release fraction to wastewater from wide dispersive use:	1.0E-05
Release fraction to soil from wide dispersive use (regional only):	1.0E-05
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	94.1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	3.5E+05
Assumed domestic sewage treatment plant flow (m <sup>3</sup> /d)	2000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	

**Safety Data Sheet**

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

**SECTION 3 EXPOSURE ESTIMATION****Section 3.1 - Health**

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**Section 3.2 - Environment**

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

**SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO****Section 4.1 - Health**

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.  
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

**Section 4.2 - Environment**

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org/en/reach-for-industries-libraries.html>).